



Puur floors limited  
Bentinck House 3-8 Bolsover St.  
London W1W 5BB

tel: 0207 118 9100  
e: [info@puurfloors.com](mailto:info@puurfloors.com)  
w: [www.puurfloors.com](http://www.puurfloors.com)

Specification Sheet

## Puur Microcrete

### Trowelled cementitious overlay flooring system

---

#### NBS category M – surface finishes

- Polymer modified cementitious screed
- Applied sand / cement screed, levelling screed, concrete at less than 5% moisture content, stone slabs, ply (to spec) or interlocking cement board
- Colour: natural white pigmented to shade.

#### Application

- Sand or grind of local irregularities in the existing substrate
- Make good any defects, cracks in the substrate using approved methods
- Remove dust and debris
- Prime area to manufacturers instruction
- Microcrete mix to manufacturers instruction
- Trowel build-up in layers
- Allow 12 hour (or overnight cure period) between layers
- Application of Puur PU seal

<b>Installation</b>	Standard 3-4mm (nominal 1-2mm - maximum 5mm)
<b>Colour</b>	Natural white or pigmented with RAL or NCS base colours
<b>Slip resistance</b>	dry R12
<b>Slip resistance</b>	wet R11

#### Substrate

Flatness / surface regularity: Max permissible deviation SR2 generally