



Puur floors limited
Bentinck House 3-8 Bolsover St.
London W1W 5BB

tel: 0207 118 9100
e: info@puurfloors.com
w: www.puurfloors.com

Specification Sheet

Puur Mono / Duo

Poured resin flooring system

NBS category M – surface finishes, resin flooring

- Polyurethane poured resin
- System comprises 100% recycled rubber crumb matting 5mm (optional), scratch coat, main levelling base 2-3 mm and two surface finishing coats.
- Applied sand / cement screed, levelling screed, concrete at less than 5% moisture content, stone slabs, ply (to spec) or interlocking cement board
- Colour: manufactured to NCS or RAL classic shades
- Regular satin sheen or with additional slip resistant coat (textured / clear spheres)

Application

- Sand or grind of local irregularities in the existing substrate
- Make good any defects using approved methods
- Remove dust and debris
- Prime area to manufacturers instruction
- Resin mix to manufacturers instruction
- Allow 12 hour (or overnight cure period)
- Application of Puur seal – 2 coats with 12 hour / overnight cure for each

Installation	Standard 2-3mm (or 8mm with matting layer)
Colour	Matched to RAL or NCS base colours (bright white or RAL white only, no 'shades of white')
Slip resistance	regular finish dry R12
Slip resistance	regular finish wet R10

Substrate

Level and to falls only not exceeding 15 degrees from horizontal
Flatness / surface regularity: Max permissible deviation SR2 generally